

Coaxial Low Pass Filter

VLF-1700

Typical Performance Data

FREQ. (MHz)	INSERTION LOSS (dB)			INPUT RETURN LOSS (dB)			OUTPUT RETURNLOSS (dB)		
	@ -55° C	@ +25° C	@ +100° C	@ -55° C	@ +25° C	@ +100° C	@ -55° C	@ +25° C	@ +100° C
50	0.04	0.05	0.06	45.66	43.91	42.71	49.33	44.41	41.25
100	0.04	0.07	0.09	40.81	43.22	44.28	41.13	40.49	39.82
500	0.13	0.21	0.24	28.24	26.87	25.62	26.75	25.48	24.32
1000	0.25	0.33	0.39	22.64	22.11	21.62	21.91	21.24	20.70
1200	0.28	0.39	0.47	22.49	22.30	22.21	22.15	21.89	21.61
1500	0.40	0.54	0.64	28.37	28.40	29.10	31.14	32.37	35.30
1600	0.47	0.61	0.77	28.12	26.96	26.09	32.02	31.03	29.79
1700	0.58	0.77	0.94	21.69	20.73	19.88	22.01	21.18	20.21
1750	0.69	0.89	1.08	18.54	17.88	17.11	18.65	17.95	17.11
1785	0.78	1.00	1.20	16.67	16.10	15.47	16.70	16.09	15.31
1930	1.51	1.89	2.26	10.36	10.04	9.77	9.93	9.41	8.87
2000	2.31	2.83	3.40	7.85	7.70	7.53	7.25	6.82	6.38
2050	3.28	3.98	4.75	6.28	6.23	6.17	5.51	5.15	4.81
2070	3.78	4.57	5.43	5.64	5.64	5.65	4.83	4.51	4.23
2100	4.77	5.73	6.75	4.84	4.90	5.00	3.93	3.68	3.50
2160	7.60	8.92	10.36	3.55	3.76	3.96	2.48	2.43	2.40
2220	11.91	13.71	15.63	2.71	3.01	3.25	1.62	1.69	1.80
2260	15.79	18.03	20.38	2.35	2.64	2.88	1.30	1.46	1.59
2295	20.06	22.72	25.59	2.09	2.37	2.59	1.13	1.32	1.49
2320	23.75	26.87	30.12	1.96	2.22	2.45	1.08	1.27	1.45
2375	34.95	36.86	36.05	1.65	1.88	2.10	0.97	1.17	1.36
2400	37.94	36.15	34.59	1.54	1.78	1.97	0.94	1.14	1.34
2500	32.90	33.29	33.94	1.17	1.38	1.57	0.88	1.09	1.28
2605	37.07	38.73	40.74	0.92	1.11	1.28	0.81	1.01	1.19
2700	49.18	50.96	49.30	0.74	0.95	1.13	0.73	0.93	1.10
2995	37.68	37.87	38.13	0.51	0.72	0.89	0.58	0.76	0.87
3400	44.42	45.41	46.43	0.41	0.60	0.75	0.45	0.56	0.67
3755	64.56	61.19	58.69	0.37	0.54	0.68	0.30	0.43	0.52
4000	50.27	49.80	49.39	0.34	0.51	0.65	0.29	0.40	0.50
4500	44.24	44.19	44.13	0.28	0.48	0.62	0.19	0.33	0.43
5500	39.32	39.34	39.53	0.21	0.41	0.61	0.16	0.31	0.47
6000	39.36	39.82	40.43	0.17	0.39	0.59	0.14	0.28	0.46
6320	43.51	45.00	47.40	0.19	0.42	0.64	0.13	0.31	0.51
6500	52.57	53.35	48.21	0.18	0.41	0.63	0.13	0.31	0.51
6550	52.36	48.11	43.78	0.18	0.43	0.66	0.15	0.33	0.52
6700	39.60	37.06	34.68	0.16	0.41	0.64	0.14	0.34	0.54
7000	25.14	23.20	21.19	0.23	0.52	0.84	0.29	0.55	0.88
7210	15.20	12.72	10.45	0.64	1.32	2.34	1.07	2.16	4.31
8000	16.67	17.11	17.54	0.25	0.49	0.71	0.26	0.44	0.59
9000	17.29	17.55	17.82	0.14	0.39	0.57	0.25	0.43	0.54

REV. X1
VLF-1700
070924

Page 1 of 1



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS 9100 CERTIFIED • RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see

